

Product availability : Stock - Normally stocked in distribution facility



Price\*\* : 257.92 USD



## Main

Product	Surge protection device
Range	Square D

## Complementary

Surge Current	40 kA per phase
Voltage Rating	600Y/347 V AC
Number of Phases	3 phase
Wiring Configuration	4-wire
MCOV	510 V
Nominal Discharge Current	10 kA
SCCR	200 kA
Local Signalling	Status LED green normal operation
Height	76.20 mm (3 in)
Width	91.44 mm (3.6 in)
Depth	86.36 mm (3.4 in)

## Environment

Enclosure Rating	NEMA 4X
Enclosure Material	black plastic
Standards	UL 1449:ed. 4 type I NEC 285 type I CSA C22.2 No 8
Ambient Operating	149 °F (65 °C)

## Ordering and shipping details

Category	08462 - SURGE PROTECTION SDSA
Discount Schedule	DE1B

GTIN	00785901210887
Package weight(Lbs)	0.35 kg (0.78 lb(US))
Returnability	Yes
Country of origin	MX

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: DINP and DIDP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.

### Contractual warranty

Warranty	18 months
----------	-----------

Approximate Dimensions

